

- **Unique identification code of the product-type:**

OLIVÉ C-94

---

- **Intended use/uses:**

Sealant for joints on the external and internal side of facade elements (intended for use in cold climates: -30°C):  
EN 15651-1; **type F-EXT-INT-CC, class 25HM**

Sealant for sanitary joints:  
EN 15651-3; **type S, class XS1**

---

- **Manufacturer:**

OLIVÉ QUÍMICA, S.A.  
Av. Bertrán Güell, 78. Apdo.nº33.  
E-08850 GAVÁ (Barcelona)  
SPAIN

---

- **System or systems of assessment and verification of constancy of performances (AVCP):**

System 3 for the type testing.  
System 3 for the reaction to fire.

---

- **Harmonised standard:**

EN 15651-1 :2012 / EN 15651-3 :2012

**Notified body/ies:**

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

---

## Declared performance/s:

<u>Essential characteristics</u>	<u>Declared Performance</u>	<u>Harmonised technical specification</u>
<b>Reaction to fire:</b> (EN 13501-1:2007 + A1:2010)	Class E	EN 15651-1,-3 :2012
<b>Release of chemicals dangerous to the environment and health:</b>	See product safety data sheet	
<b>Water tightness and air tightness as determined by:</b>		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	EN 15651-1,-3 :2012
• Loss of volume (EN ISO 10563)	≤ 10 %	EN 15651-1,-3 :2012
• Tensile properties (i.e. at maintained extension) at -30°C (modif. EN ISO 8340)	NF	EN 15651-1 :2012
• Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	EN 15651-1,-3 :2012
• Microbiological growth (EN ISO 846, proc.B)	0	EN 15651-3 :2012
<b>Durability:</b>	Pass	EN 15651-1,-3 :2012

Conditioning: Method A / NF = No Failure  
Substrates: Anodized aluminium and mortar-M2, without primer.

## Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Gavà, Barcelona (Spain)  
02 / 05 / 2017



José M. Martínez  
Technical Manager

**Disclaimer:** The information contained in this DoP is provided in good faith and deemed accurate at the date of publication of this document. Despite the intended uses specified in this document and due to the different conditions of use, the user is obliged to ensure the product is suitable for its particular application and is legally compliant for it. This information should not be construed as legal advice. Olive Química makes no warranty express or implied regarding the fitness of the Product for any particular purpose. It is over understood that we warranty the irreproachable quality of our products in accordance with our General Conditions of Sales and Supply.

 <b>1292</b>	
OLIVÉ QUÍMICA, S.A., Av. Bertrán Güell, 78, 08850 Gavá (Barcelona), Spain. 16 <b>OQ-1616311</b>	
EN 15651-1 : F-EXT-INT-CC EN 15651-3 : XS1 <b>OLIVÉ C-94</b> Sealant for facade elements (for exterior and interior application), also in cold climates and for sanitary joints.	
Conditioning: Method A Substrates: Anodized aluminium and mortar-M2, without primer.	
<b>REACTION TO FIRE:</b>	Class E
<b>RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH:</b>	See product safety data sheet
<b>WATER TIGHTNESS AND AIR TIGHTNESS AS DETERMINED BY:</b>	
• Resistance to flow:	≤ 3 mm
• Loss of volume:	≤ 10%
• Tensile properties (i.e. at maintained extension) at -30°C:	NF
• Tensile properties at maintained extension after water immersion:	NF
• Microbiological growth:	0
<b>DURABILITY:</b>	Pass

NF = No failure